



ROCKWELL / ROCKWELL SUPERFICIAL HARDNESS TESTER MODEL : FRET

Test loads - 15,30,45kgf for superficial scale & 60,100,150kgf for Rockwell ABC scale. Digital Display with 0.1 Rockwell Resolution. Loading / Unloading Cycle Automatic by a push button operation. Optional - Printer facility.



ROCKWELL SYSTEM HARDNESS TESTER MODEL - RASN (E)

Test loads - 60,100.& 150 kgf for test on Rockwell A,B,C scale Loading / Unloading Cycle Automatic by a push button operation. Raising / lowering of elevating spindle - Manual. Electronic Digital readout with 0.1 Rockwell resolution. Go-nogo facility with presettable & higher limits. Optional - Printer facility. Capacity - Throat - 133mm, Max.test-230mm



ROCKWELL SYSTEM HARDNESS TESTER MODEL - RASN

Test loads - 60,100,& 150 kgf for tests on Rockwell A,B,C scale Automatic zero setting dial gauge. Load selection just by a dialing externally. Capacity - Throat - 133mm, Max.test-230mm Conform to IS:3804, BS:891 & ASTM:E-18



VICKERS HARDNESS TESTER MODEL : MVM 50

Testing range is very wide. from soft metal such as lead. upto the hardest like hardened steel. Same hardness number is obtained on the same specimen, regardless of the load applied. The indentation is tiny and allows testing of a precision finished part. Loading & unloading cycle is motorised. Thin sheet metal is perfectly tested because the load applied is very small. Built-in projection screen to get accurate results. Test loads - 5,10,20,30 & 50kgf. Optional magnification - 70 x Scale least count 0.001mm Capacity - Throat 135mm, Max. Test height 200 mm



ROCKWELL SYSTEM HARDNESS TESTER MODEL : RAS

Test loads 60, 100 & 150 kgf for tests on Rockwell A,B,C scale. Automatic zero setting dial gauge. Load selection just by dialing externally. Capacity-Throat 133mm Max. test height 230mm Conmfirm to IS:3804, BS: 891 & ASTM:E-18



ROCKWELL CUM BRINELL SUPERFICIAL HARDNESS TESTER MODEL : RAB-250

Test loads 60, 100 & 150 kgf for Rockwell test and 187.5 & 250 kgf for Brinell tests. Automatic zero setting dial gauge. Load selection just by dialing externally. Capacity-Throat 150mm Max. test height 295mm Conmfirm to IS:3804, BS: 891 & ASTM:E-18 for Brinell tests.



ROCKWELL CUM ROCKWELL SUPERFICIAL HARDNESS TESTER MODEL : TWIN

Test loads 60, 100 & 150 kgf for Rockwell test and 15,30 & 45 kgf for Rockwell superficial tests. Automatic zero setting dial gauge. Capacity-Throat 150mm Max. test height 295mm Conmfirm to IS:3804, BS: 891 & ASTM:E-18 for Rockwell tests and IS:5073, ASTM: E18 for Rockwell superficial tests.



BRINELL HARDNESS TESTER MODEL : B3000 (H)

Test loads 500 to 3000 kgf in steps of 250 kgf. Capacity - Throat 200 mm. Max test height - 410mm Hydraulic power pack & control circuit for effortless loading/unloading operation. Facilitates production testing within tolerance limits as set on dial gauge. Conform to IS:2281, BS:240 & ASTM:E10.



BRINELL HARDNESS TESTER MODEL : B3000 (O)

Test loads 500 to 3000 kgf in steps of 250 kgf. Capacity - Throat 200 mm. Max test height - 380mm Hydraulic power pack & control circuit for effortless loading/unloading operation. Built in optical system with 14 x magnification. Dia of impression measured under test position with an accuracy 0.1mm Conform to IS:2281, BS:240, & ASTM:E10

MANUFACTURED BY :



MICRO CONTROL SYSTEMS

Ward No. 24/1264/5, Vitthal Nagar, Shahapur Road, ICHALKARANJI - 416 115. Maharashtra (INDIA)

● Tel.: 0230 - 2425674 ● Fax : 0230 - 2421966
● E-mail : klp_mcs@sancharnet.in

SOLD & SERVICED BY :